


EC210L



结构:

- 合成橡胶内层，二层钢丝编织增强层，黑色合成橡胶外层。MSHA 认证。

特征:

- 符合或超过: SAE 100R2AT Type S, EN853, 2SN

工作温度范围:

- -40°C 到+100°C (-40°F 到+212°F)

应用:

- 石油基或水基液压油的液压系统， 适用各种工业行业。

技术参数:

零件号 Part No.	软管内径 Hose I.D.		软管外径 Hose O.D		最大工作压力 Max Working Pressure		爆破压力 Burst Pressure		最小弯曲半径 Min Bend Radius		软管重量 Weight	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs/ft
EC210-04L	6.4	0.25	15	0.59	400	5,800	1,600	23,200	100	3.94	0.38	0.26
EC210-05L	7.9	0.31	16.5	0.65	350	5,100	1,400	20,400	115	4.53	0.43	0.29
EC210-06L	9.5	0.38	18.9	0.74	330	4,800	1,320	19,200	130	5.12	0.54	0.36
EC210-08L	12.7	0.5	22.2	0.87	275	4,000	1,100	16,000	180	7.09	0.64	0.43
EC210-10L	15.9	0.62	25.2	0.99	250	3,650	1,000	14,600	200	7.87	0.75	0.5
EC210-12L	19	0.75	29.2	1.15	215	3,125	860	12,500	240	9.45	0.93	0.62
EC210-16L	25.4	1	37.2	1.46	165	2,400	660	9,600	300	11.81	1.29	0.87
EC210-20L	31.8	1.25	47.3	1.86	125	1,800	500	7,200	420	16.54	1.89	1.27
EC210-24L	38.1	1.5	53.7	2.11	90	1,300	360	5,200	500	19.69	2.1	1.41
EC210-32L	50.8	2	66.7	2.63	80	1,150	320	4,600	630	24.8	2.76	1.85