

EC215L



结构:

- 合成橡胶内层，二层钢丝编织增强层，黑色合成橡胶外层。MSHA 认证

特征:

- 符合或超过: EN857 2SC

工作温度范围:

- -40°C 到+100°C (-40°F 到+212°F)

应用:

- 石油基或水基液压油的液压系统， 适用各种工业行业。

技术参数:

零件号 Part No.	软管内径 Hose I.D.		软管外径 Hose O.D.		最大工作压力 Max Working Pressure		爆破压力 Burst Pressure		最小弯曲半径 Min Bend Radius		软管重量 Weight	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs/ft
EC215-04L	6.4	0.25	13.2	0.52	400	5,800	1,600	23,200	75	1.97	0.28	0.19
EC215-05L	7.9	0.31	15	0.59	350	5,100	1,400	20,400	85	2.17	0.33	0.22
EC215-06L	9.5	0.38	17.1	0.67	330	4,800	1,320	19,200	90	2.56	0.41	0.28
EC215-08L	12.7	0.5	20.7	0.81	275	4,000	1,100	16,000	130	3.54	0.57	0.38
EC215-10L	15.9	0.62	23.8	0.94	250	3,650	1,000	14,600	170	3.94	0.68	0.46
EC215-12L	19	0.75	27.7	1.09	215	3,125	860	12,500	200	4.72	0.81	0.54
EC215-16L	25.4	1	35.5	1.4	165	2,400	660	9,600	250	5.91	1.17	0.79
EC215-20L	31.8	1.25	43.6	1.72	125	1,800	500	7,200	250	9.84	1.56	1.05
EC215-24L	38.1	1.5	50.7	2	100	1,450	400	5,800	300	11.81	1.81	1.22