

2781



结构:

- 合成橡胶内层，两层钢丝编织增强层，Dura-Tuff™ 高耐磨合成橡胶外层。

特征:

- HI-IMPULSE 二层钢丝编织软管
- 符合或超过: SAE 100R2A、EN853 2ST、ISO 1436-1 2ST 型

工作温度范围:

- -40°C 到+100°C (-40°F 到+212°F)

应用:

- 石油基或水基液压油的液压系统， 适用各种工业行业。

技术参数:

零件号 Part No.	软管内径 Hose I.D.		软管外径 Hose O.D.		最大工作压力 Max Working Pressure		爆破压力 Burst Pressure		最小弯曲半径 Min Bend Radius		软管重量 Weight	
	mm	in	mm	in	bar	psi	bar	psi	mm	in	Kg/m	lbs/ft
278104	6.4	0.25	17.5	0.69	400	5,800†	1,600	23,200†	101.6	4	0.5	0.33
					345	5,000	1,380	20,000				
2781-06	9.7	0.38	21.3	0.84	345	5,000†	1,380	20,000†	127	5	0.67	0.45
					280	4,000	1,120	16,000				
2781-8	12.7	0.5	24.6	0.97	295	4,300†	1,180	17,200†	177.8	7	0.83	0.56
					241	3,500	964	14,000				
2781-10	16	0.63	27.7	1.09	250	3,650†	1,000	14,600†	203.2	8	0.97	0.62
					190	2,750	760	11,000				
2781-12	19.1	0.75	31.8	1.25	215	3,100†	860	12,400†	241.3	9.5	1.19	0.8
					155	2,250	620	9,000				
2781-16	25.4	1	39.6	1.56	175	2,550†	700	10,200†	304.8	12	1.58	1.06

					138	2,000	552	8,000				
2781-20	31.8	1.25	50.8	2	155	2,250†	620	9,000†	419.1	16.5	2.57	1.73
					112	1,625	448	6,500				
2781-24	38.1	1.5	57.2	2.25	125	1,800†	500	7,200†	508	20	3.05	2.05
					86	1,250	344	5,000				
2781-32	50.8	2	69.9	2.75	90	1,300†	360	5,200†	635	25	4.02	2.7
					78	1,125	312	4,500				